

SAFETY DATA SHEET

Date Printed: 05/16/2024 Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifier: (3N5) 99.95% Molybdenum Selenide Sputtering Target

Product Code: MO-SE-035-ST

CAS Number: 12058-18-3

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551 Fax: +1 310-208-0351 Emergency telephone number: +1 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Specific target organ toxicity - repeated exposure (Category 2), H373 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410 GHS Label elements, including precautionary statements Pictogram



Signal word Danger Hazard statement(s) H301 + H331 Toxic if swallowed or if inhaled H373 May cause damage to organs through prolonged or repeated exposure. H410 Very toxic to aquatic life with long lasting effects. Precautionary statement(s) P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.

P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician.

P314 Get medical advice/ attention if you feel unwell.

P391 Collect spillage.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances Formula : MoSe2 CAS-No. : 12058-18-3 EC-No. : 235-027-9 Index-No. : 034-002-00-8 Hazardous components Component: Molybdenum(IV) selenide Classification: Acute Tox. 3; STOT RE 2; Aquatic Acute 1; Aquatic Chronic 1; H301 + H331, H373, H410 Concentration: <= 100 %

SECTION 4. FIRST AID MEASURES

Description of first aid measures General advice Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. If inhaled If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician. In case of skin contact Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician. In case of eye contact Flush eyes with water as a precaution. If swallowed Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Special hazards arising from the substance or mixture Selenium/selenium oxides, Molybdenum oxides Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary. Further information No data available

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8. Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided. Methods and materials for containment and cleaning up Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal. Reference to other sections For disposal see section 13.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols.Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2. Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Moisture sensitive. Storage class (TRGS 510): Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects Specific end use(s) Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems: Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. **Control parameters** Components with limit values that require monitoring at the workplace: Selenium and selenium compounds (as Se) mg/m3 ACGIH TLV 0.2 Austria MAK 0.1 Belgium TWA 0.2 Denmark TWA 0.1 Finland TWA 0.1; 0.3-STEL Germany MAK 0.1 Hungary 0.1-STEL Ireland TLV 0.1 Japan OEL 0.1 Korea TLV 0.2 Netherlands MAC-TGG 0.1 Poland TWA 0.1; 0.3-STEL Sweden NGV 0.1 Switzerland MAK-W 0.1 United Kingdom TWA 0.1 USA PEL 0.2 Selenium and selenium compounds (as Se) mg/m3 ACGIH TLV 0.2 Austria MAK 0.1 Belgium TWA 0.2 Denmark TWA 0.1 Finland TWA 0.1; 0.3-STEL Germany MAK 0.1 Hungary 0.1-STEL Japan OEL 0.1 Korea TLV 0.2 Netherlands MAC-TGG 0.2 Poland TWA 0.1; 0.3-STEL Sweden NGV 0.1 Switzerland MAK-W 0.1 United Kingdom TWA 0.1 USA PEL 0.2 Molybdenum and compounds (as Mo) mg/m3 ACGIH TLV 10(Mo) Austria MAK 15(Mo) Denmark TWA 10(Mo) Finland TWA 5(Mo) Germany MAK 15(Mo) Korea TLV 10(Mo) Poland TWA 4(Mo); 10(Mo)-STEL Sweden NGV 10(Mo)(total dust); 5(Mo)(resp. dust) Switzerland MAK-W 10(Mo) United Kingdom TWA 10(Mo); 20(Mo)-STEL OSHA PEL 15(Mo)(total dust)

Exposure controls Appropriate engineering controls Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Personal protective equipment Eye/face protection Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Skin protection Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. **Body Protection** Complete suit protecting against chemicals. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Respiratory protection Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N99 (US) or type P2 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Control of environmental exposure Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Additional information: No data

Information on basic physical and chemical properties **General Information** Appearance: Form: Powder Color: Dark grey Odor: Odorless Odor threshold: Not determined. pH-value: Not applicable. Melting point/Melting range: 1200 °C (2192 °F) Boiling point/Boiling range: Not determined Sublimation temperature / start: Not determined Flash point: Not applicable Flammability (solid, gaseous): Not determined. Ignition temperature: Not determined Decomposition temperature: Not determined Auto igniting: Not determined. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined

Upper: Not determined Vapor pressure: Not applicable. Density at 20 °C (68 °F): 6 g/cm³ (50.07 lbs/gal) Relative density Not determined. Vapor density Not applicable. Evaporation rate Not applicable. Solubility in / Miscibility with Water: Insoluble Partition coefficient (n-octanol/water): Not determined. Viscosity: dynamic: Not applicable. kinematic: Not applicable. Other information No further relevant information available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity No data available Chemical stability Stable under recommended storage conditions. Possibility of hazardous reactions No data available Conditions to avoid No data available Incompatible materials Hydrogen peroxideStrong oxidizing agents Hazardous decomposition products Other decomposition products - No data available In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects Acute toxicity No data available Inhalation: No data available Dermal: No data available No data available Skin corrosion/irritation No data available Serious eye damage/eye irritation No data available Respiratory or skin sensitisation No data available Germ cell mutagenicity No data available Carcinogenicity IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Molybdenum(IV) selenide, -325 mesh) ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a Reproductive toxicity No data available No data available Specific target organ toxicity - single exposure No data available Specific target organ toxicity - repeated exposure No data available Aspiration hazard No data available Additional Information **RTECS:** Not available To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No further relevant information available. Persistence and degradability No further relevant information available. Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available. Ecotoxical effects: Remark: Very toxic for aquatic organisms Additional ecological information: General notes: Do not allow material to be released to the environment without proper governmental permits. Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. May cause long lasting harmful effects to aquatic life. Avoid transfer into the environment. Very toxic for aquatic organisms Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. Other adverse effects No further relevant information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods Product Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Contaminated packaging Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

DOT (US) UN number: 3288 Class: 6.1 Packing group: III Proper shipping name: Toxic solid, inorganic, n.o.s. Reportable Quantity (RQ): Poison Inhalation Hazard: No IMDG UN number: 3288 Class: 6.1 Packing group: III EMS-No: F-A, S-A Proper shipping name: TOXIC SOLID, INORGANIC, N.O.S. (Molybdenum(IV) selenide) Aldrich - 778087 Page 7 of 8 Marine pollutant: yes IATA UN number: 3288 Class: 6.1 Packing group: III Proper shipping name: Toxic solid, inorganic, n.o.s. (Molybdenum(IV) selenide)

SECTION 15. REGULATORY INFORMATION

SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313: Molybdenum(IV) selenide CAS-No. 12058-18-3 **Revision Date** 2007-07-01 SARA 311/312 Hazards Acute Health Hazard Massachusetts Right To Know Components No components are subject to the Massachusetts Right to Know Act. Pennsylvania Right To Know Components Molybdenum(IV) selenide CAS-No. 12058-18-3 **Revision Date** 2007-07-01 New Jersey Right To Know Components Molybdenum(IV) selenide CAS-No. 12058-18-3 **Revision Date** 2007-07-01 California Prop. 65 Components This product does nnot contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.