

SAFETY DATA SHEET

Date Printed: 05/18/2024 Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifier: (5N) 99.999% Lead Naphthenate

Product Code: PB-NAPH-05

CAS Number: 61790-14-5

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551 Fax: +1 310-208-0351 Emergency telephone number: +1 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classification: This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Flammable liquids Category 3 Acute oral toxicity Category 4 Acute Inhalation Toxicity - Vapors Category 4 Germ Cell Mutagenicity Category 1B Carcinogenicity Category 1B **Reproductive Toxicity Category 1A** Specific target organ toxicity - (repeated exposure) Category 1 Aspiration Toxicity Category 1 Signal Word: Danger Hazard Statements: Flammable liquid and vapor Harmful if swallowed May be fatal if swallowed and enters airways Harmful if inhaled May cause genetic defects May cause cancer May damage the unborn child. Suspected of damaging fertility Causes damage to organs through prolonged or repeated exposure



Precautionary Statements Prevention: Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge Response: IF exposed or concerned: Get medical attention/advice Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower Ingestion: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting Rinse mouth Fire: In case of fire: Use CO2, dry chemical, or foam for extinction Storage: Store locked up Store in a well-ventilated place. Keep cool Disposal: Dispose of contents/container to an approved waste disposal plant Hazards not otherwise classified (HNOC): Very toxic to aquatic life with long lasting effects Repeated exposure may cause skin dryness or cracking

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component / CAS-No: Lead naphthenate / 61790-14-5 Stoddard solvent / 8052-41-3

SECTION 4. FIRST AID MEASURES

General Advice: If symptoms persist, call a physician. Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact:

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation:

Move to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs.

Ingestion:

Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting. Call a physician or Poison Control Center immediately. If vomiting occurs naturally, have victim lean forward. Most important symptoms and effects:

Breathing difficulties. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Notes to Physician:

Treat symptomatically

SECTION 5. FIREFIGHTING MEASURES

Suitable Extinguishing Media: Cool closed containers exposed to fire with water spray. Unsuitable Extinguishing Media: No information available Flash Point 40 °C / 104 °F Method - No information available Autoignition Temperature: No information available **Explosion Limits** Upper No data available Lower No data available Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available Specific Hazards Arising from the Chemical: Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire fighting to enter drains or water courses. Hazardous Combustion Products: None known Protective Equipment and Precautions for Firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. NFPA: Health 3 Flammability 2 Instability Physical hazards

Personal Precautions:

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions:

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods for Containment and Clean Up:

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

SECTION 7. HANDLING AND STORAGE

Handling:

Wear personal protective equipment. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges. Storage:

Store under an inert atmosphere. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines Component: Lead naphthenate ACGIH TLV: OSHA PEL: NIOSH IDLH: IDLH: 100 mg/m3 TWA: 0.050 mg/m3 Mexico OEL (TWA): Component: Stoddard solvent ACGIH TLV: TWA: 100 ppm OSHA PEL: (Vacated) TWA: 100 ppm; (Vacated) TWA: 525 mg/m3; TWA: 500 ppm; TWA: 2900 mg/m3 NIOSH IDLH: IDLH: 20000 ma/m3 TWA: 350 ma/m3 Ceiling: 1800 ma/m3 Mexico OEL (TWA): TWA: 100 ppm; TWA: 523 mg/m3 STEL: 200 ppm; STEL: 1050 mg/m3 **Engineering Measures:** Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Personal Protective Equipment Eye/face Protection: Wear appropriate protective evenlasses or chemical safety goggles as described by OSHA's eve and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Skin and body protection: Long sleeved clothing. Respiratory Protection: Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Hygiene Measures:

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid Appearance Brown Odor oilv Odor Threshold No information available pH No information available Melting Point/Range No data available Boiling Point/Range No information available Flash Point 40 °C / 104 °F Evaporation Rate No information available Flammability (solid,gas) Not applicable Flammability or explosive limits Upper No data available Lower No data available Vapor Pressure No information available Vapor Density No information available Specific Gravity 1.13 g/cm3 Solubility No information available Partition coefficient: n-octanol/water No data available Autoignition Temperature No information available Decomposition Temperature No information available Viscosity No information available

SECTION 10. STABILITY AND REACTIVITY

Reactive Hazard: None known, based on information available Stability: Air sensitive. Conditions to Avoid: Keep away from open flames, hot surfaces and sources of ignition. Incompatible Materials: Strong oxidizing agents Hazardous Decomposition Products: None under normal use conditions Hazardous Polymerization: Hazardous Polymerization does not occur. Hazardous Reactions: None under normal processing.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity Product Information Oral LD50 Category 4. ATE = 300 - 2000 mg/kg. Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Vapor LC50 Category 4. ATE = 10 - 20 mg/l. Toxicologically Synergistic Products: No information available Delayed and immediate effects as well as chronic effects from short and long-term exposure Irritation: No information available

Sensitization: No information available Carcinogenicity: Component / CAS-No: Lead naphthenate / 61790-14-5 IARC: Not listed NTP: Reasonably Anticipated ACGIH: Not listed OSHA: X Mexico: Not listed Component / CAS-No: Stoddard solvent / 8052-41-3 IARC: Not listed NTP: Not listed ACGIH: Not listed **OSHA:** Not listed Mexico: Not listed Mutagenic Effects: No information available Reproductive Effects: No information available. Developmental Effects: No information available. Teratogenicity: No information available. STOT - single exposure None known STOT - repeated exposure None known Aspiration hazard: No information available Symptoms / effects, both acute and delayed: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting Endocrine Disruptor Information: No information available Other Adverse Effects: The toxicological properties have not been fully investigated.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity:

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Persistence and Degradability: Immiscible with water

Bioaccumulation/ Accumulation: No information available.

Mobility: Is not likely mobile in the environment due its low water solubility.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

SECTION 14. TRANSPORT INFORMATION

DOT UN-No UN1993 Proper Shipping Name FLAMMABLE LIQUID, N.O.S. Proper technical name (lead naphthenate in mineral spirits) Hazard Class 3 Packing Group III TDG UN-No UN1993 Proper Shipping Name FLAMMABLE LIQUID, N.O.S. Hazard Class 3 Packing Group III IATA UN-No UN1993 Proper Shipping Name FLAMMABLE LIQUID, N.O.S. Hazard Class 3 Packing Group III IMDG/IMO UN-No UN1993 Proper Shipping Name Flammable liquid, n.o.s. Hazard Class 3 Packing Group III

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations TSCA 12(b): Not applicable **SARA 313** Component: Lead naphthenate CAS-No: 61790-14-5 Weight: 61.00 % SARA 313 - Threshold Values: 1.0 % CWA (Clean Water Act) Component: Lead naphthenate CWA - Hazardous Substances: -CWA - Reportable Quantities: -CWA - Toxic Pollutants: X CWA - Priority Pollutant: -Clean Air Act Component: Lead naphthenate HAPS Data: X Class 1 Ozone Depletors: Class 2 Ozone Depletors: U.S. Department of Transportation Reportable Quantity (RQ): N **DOT Marine Pollutant N DOT Severe Marine Pollutant N** U.S. Department of Homeland Security: This product does not contain any DHS chemicals.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED

GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.