

SAFETY DATA SHEET

Date Printed: 05/14/2024 **Date Revised:** 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifier: >95% Thallium(I) Ethoxide

Product Code: TL1-ETOX-015-LIQ

CAS Number: 20398-06-5

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551 Fax: +1 310-208-0351

Emergency telephone number:

+1 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Acute toxicity, Oral (Category 2), H300 Acute toxicity, Inhalation (Category 2), H330 Specific target organ toxicity - repeated exposure (Category 2), H373 Acute aquatic toxicity (Category 2), H401 Chronic aquatic toxicity (Category 2), H411

2.2 GHS Label elements, including precautionary statements



Pictogram

Signal word Danger

Hazard statement(s)

H300 + H330 Fatal if swallowed or if inhaled

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P260 Do not breathe dust/ fume/ gas/ mist/ Vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P284 Wear respiratory protection.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.

P314 Get medical advice/ attention if you feel unwell.

P391 Collect spillage.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms: Thallous ethoxide

Formula: C2H5OTI

Molecular weight: 249.44 g/mol

CAS-No.: 20398-06-5 EC-No.: 243-786-2 Index-No.: 081-002-00-9 Hazardous components

Component Classification Concentration

Thallium(I) ethoxide Acute Tox. 2; STOT RE 2; Aquatic Acute 2; Aquatic Chronic 2; H300 + H330,

H373, H411 <= 100 %

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2)

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Nature of decomposition products not known.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing Vapors, mist or gas. Ensure adequate ventilation.

Evacuate personnel

to safe areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment

must be avoided.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for

disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of Vapor or mist.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C

Moisture sensitive.

Storage class (TRGS 510): Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component CAS-No. Value Control

parameters

Basis

Thallium(I) ethoxide 20398-06-5 TWA 0.100000

mg/m3

USA. Occupational Exposure Limits

(OSHA) - Table Z-1 Limits for Air

Contaminants

Remarks Skin designation

TWA 0.100000

mg/m3

USA. ACGIH Threshold Limit Values

(TLV)

Alopecia

Adopted values or notations enclosed are those for which changes

are proposed in the NIC

2010 Revision or addition to the notice of intended changes

See Notice of Intended Changes (NIC)

Danger of cutaneous absorption

varies

TWA 0.020000

mg/m3

USA. ACGIH Threshold Limit Values

(TLV)

Peripheral neuropathy

Gastrointestinal damage

Danger of cutaneous absorption

varies

TWA 0.1 mg/m3 USA. Occupational Exposure Limits

(OSHA) - Table Z-1 Limits for Air

Contaminants

Skin designation

TWA 0.02 mg/m3 USA. ACGIH Threshold Limit Values

(TLV)

Peripheral neuropathy

Gastrointestinal damage

Danger of cutaneous absorption

varies

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate

government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique

(without

touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after

use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to

the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose

combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and

components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- 9.1 Information on basic physical and chemical properties
- a) Appearance Form: liquid

Colour: yellow

- b) Odor No data available
- c) Odor Threshold No data available
- d) pH No data available
- e) Melting point/freezing

point

No data available

f) Initial boiling point and

boiling range

No data available

- g) Flash point 113 °C (235 °F) closed cup
- h) Evaporation rate No data available
- i) Flammability (solid, gas) No data available
- j) Upper/lower

flammability or

explosive limits

No data available

- k) Vapor pressure No data available
- I) Vapor density No data available
- m) Relative density 3.522 g/cm3 at 25 °C (77 °F)
- n) Water solubility No data available
- o) Partition coefficient: noctanol/

water

No data available

p) Auto-ignition

temperature

No data available

q) Decomposition

temperature

No data available

- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available
- 9.2 Other safety information

No data available

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents, Strong acids

10.6 Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

No data available

Additional Information

RTECS: Not available

The most characteristic symptom of thallium exposure is alopecia (loss of hair). Cutaneous effects may include dry,

scaly skin and impairment of nail growth often resulting in the appearance of crescent-shaped strips across fingernails

and toenails (Mees' line). Other symptoms in acute poisoning relate chiefly to the gastrointestinal tract, nervous

system, skin, eyes, and cardiovascular system. Acute poisoning results in swelling of the feet and legs, arthralgia,

vomiting, insomnia, hyperesthesia and paresthesia of the hands and feet, mental confusion, polyneuritis with severe

pain in the legs and loins, partial paralysis of the legs, angina-like pains, nephritis, wasting and weakness, and

lymphocytosis and eosinophilia. In chronic poisoning, central and peripheral nervous system abnormalities may persist

including ataxia, tremor, incoordination, paralysis of extremities, endocrine disorders, memory loss, and psychoses

may develop., To the best of our knowledge, the chemical, physical, and toxicological properties have not been

thoroughly investigated.

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste

disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a

chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

SECTION 14. TRANSPORT INFORMATION

DOT (US)

UN number: 2810 Class: 6.1 Packing group: II

Proper shipping name: Toxic, liquids, organic, n.o.s. (Thallium(I) ethoxide)

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 2810 Class: 6.1 Packing group: II EMS-No: F-A, S-A

Proper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (Thallium(I) ethoxide)

IATA

UN number: 2810 Class: 6.1 Packing group: II

Proper shipping name: Toxic liquid, organic, n.o.s. (Thallium(I) ethoxide)

SECTION 15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Thallium(I) ethoxide

CAS-No.

20398-06-5

Revision Date

2007-07-01

SARA 311/312 Hazards

Acute Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

Thallium(I) ethoxide

CAS-No.

20398-06-5

Revision Date

2007-07-01

New Jersey Right To Know Components

Thallium(I) ethoxide

CAS-No.

20398-06-5

Revision Date

2007-07-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth

defects, or any other

reproductive harm.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.